

Ballast-Compatible or Single Ended Connection with Integrated Power Supply

Features:

- Linear LED T8 type tube with Built-in Driver
- Shatter proof housing: Polycarbonate/Aluminum
- High lumens & High CRI
- Built-in driver for easy installation
- 50,000 hour life
- DLC QPL - Design Lights Consortium Listed
- UL Listed
- 5 year limited warranty



Model	Size	Input	Frequency	Wattage	PF	CRI	Lumen	Lm/W
DIGILITE ZY-T8-15W1200	4'	100-277V	50-60Hz	14.7w	>0.99	>80	1825	>110Lm/w
DIGILITE ZY-T8-18W1200	4'	100-277V	50-60Hz	17.7w	< 0.98	>80	1980	>110Lm/w
DIGILITE ZY-T8-22W1200	4'	100-277V	50-60Hz	21.8w	< 0.99	>80	2420	>110Lm/w
DIGILITE ZY-T8-14W900*	3'	100-277V	50-60Hz	13.5w	<0.90	>80	1495	>110Lm/w
DIGILITE ZY-T8-15W600	2'	100-277V	50-60Hz	8.4w	<0.90	>80	1050	>110Lm/w

Color Options: 3000K 4000K 5000K Lens Options: Clear or Frosted Lens Lumen Output @ 5000K

*Please note: DLC has no QPL category for 3' product, please follow optional approval process for the local program.

Includes production codes: B1XX (at line voltage), BOXX, BINS, BINT, BONX, BONT, BODS, BODT, BODS, BODT

Order Codes: 4ft 18W: DL-T8-18W1200 (Color, Frosted/Clear) 4ft 22W: DL-T8-18W1200 (Color, Frosted/Clear)
 3ft 14w: DL-T8-10W900 (Color, Frosted/Clear) 2ft 10w: DL-T8-15W600 (Color, Frosted/Clear)

